

# Lycal GLR 1008



Lycal GLR 1008 is very hard Epoxy Resin use for decorating flat surface of buckle or metal trade mark.

## Component :

- Part A : Clear or colored liquid resin.  
Part B : Transparent liquid.  
Mixing Ratio : A : B = 10 : 4 by wt.  
Packing : Part A 2.5 Kg/can  
Part B 1 Kg/plastic bottle



## Application method

- 1) With the mixing ratio A:B = 10:4 by wt. Mix the AB thoroughly.
- 2) Heat the article.
- 3) Pouring the mixed A,B component to the still hot article to cover all of the pattern.
- 4) Remove the surface bubble by propane lighter.
- 5) Heated 90 °C x 2 hrs.
- 6) Polishing.
- 7) Plating (keep the plating solution under 60 °C).



東莞好利精細化工有限公司

廣東東莞大嶺山大塘管理區

電話 : 0769-83351634,83351742

傳真 : 0769-83351614

忠誠企業公司

**LOYAL ENTERPRISE CO.**

(wholly -Owned & Operated by Southfirm Ltd.)

FLATS D,E,H, 16/FL, BLOCK B, MARVEL IND. BLDG.,  
17-25 KWAI FUNG CRESCENT, KWAICHUNG N.T., H.K.

E-MAIL ADDRESS : [sales@loyalenterprise.com](mailto:sales@loyalenterprise.com)

HOME PAGE : [www.loyalenterprise.com](http://www.loyalenterprise.com)

TEL: 24297261, 24297269 FAX: 24804473